



Ø200 mm

1305 mm

6921	Lacado blanco texturado. Textured white lacquering.
6922	Lacado gris marengo. Anthracite grey lacquering.
4921	Lacado cobre metalizado. Metallic copper lacquering (D2525 Tanami sable)
4922	Lacado dorado metalizado. Metallic golden lacquering (D2525 Gundar metallic satin)



Ø200 mm | H. 1.205 mm
3 x DOB LED 5W
500 (x3) lumen | 2.700K
| CRI 90
3-step MacAdam
PF. 0,95
Dimable/ Dimmable

Clase I: Aislamiento básico
Class I: Basic insulation

Pantalla inyectada en aluminio. Pantalla difusora de la luz y protectora de los leds en policarbonato inyectado, ocupando todo el perímetro de la pantalla de aluminio dejando únicamente el espacio para los 3 leds habilitados.

Interruptor aéreo habilitado en el cable de conexión.

Base de peso de 5 mm de grosor.

Aluminium injected shade. The internal diffuser is manufactured in injected polycarbonate to cover the whole perimeter, leaving only the three direct-to-mains LEDs used in this model, visible.

Aerial switch included on connection cable.

Weight base with 5 mm width.

Accesorios / Accessories



Ø94 mm

37 mm

2400	Dimmer Aéreo Aerial dimmer
------	-------------------------------